

A range of blood bank refrigerators with single or dual compressors for reliable storage of blood bags. Type 2 refrigeration is required by BS4376 for all departments storing large numbers of blood bags. These cabinets all have triple-glazed doors. The range includes pass-through cabinets. Options include solid doors & electronic door locks with digital key code. Dual alarms (Alert!** and **Action!**) as standard as required by the MHRA.**



VRB2-140 Type 1 refrigeration only. Holds up to 60-72 bags in 3 drawers. Advanced dual point alarm system with remote alarm connections. Full data storage of up to 5 years information including all alarm alerts. Graph printout. External: 940h x 520w x 640d mm



VRB2-170 Type 1 refrigeration only. Holds up to 90-126 bags in 3 drawers. Advanced dual point alarm system with remote alarm connections. Full data storage of up to 5 years information including all alarm alerts. Graph printout. External: 1290h x 600w x 660d mm



VRB2-250 Type 1 or 2 refrigeration. Holds up to 152-168 bags in 4 drawers. Advanced dual point alarm system with remote alarm connections. Full data storage of up to 5 years information including all alarm alerts. Graph printout. External: 1530h x 600w x 780d mm



VRB2-400 Type 1 refrigeration only. Holds up to 180-210 bags in 5 drawers. Advanced dual point alarm system with remote alarm connections. Full data storage of up to 5 years information including all alarm alerts. Graph printout. External: 1960h x 600w x 660d mm



VRB2-700 Type 1 or 2 refrigeration. Holds up to 420 bags in 7 drawers. Advanced dual point alarm system with remote alarm connections. Full data storage of up to 5 years information including all alarm alerts. Graph printout. Also available in pass-through format. External: 2050h x 720w x 830d mm



VRB2-1500 Type 1 or 2 refrigeration. Holds up to 840 bags in 14 drawers. Advanced dual point alarm system with remote alarm connections. Full data storage of up to 5 years information including all alarm alerts. Graph printout. Also available in pass-through format. External: 2050h x 1440w x 820d mm

All models meet BS4376 and MHRA specification. All offer digital control with alarms for out of range conditions; remote alarm connections. The chart printout gives a permanent record of storage temperature.

Type 2 refrigeration gives protection against refrigeration failure - In normal use the two refrigeration systems alternate in use. If one compressor fails the other compressor automatically takes over control. This means that valuable blood stocks are not compromised or lost.

Other options include shelves, solid doors and keypad electronic door locks.

As part of our policy of continuous product improvement, the specifications are subject to change without notice.

VRB2 Blood Bank Fridges

Ringstones Industrial Estate, Whaley Bridge, High Peak, SK23 7PD, UK
Tel: 01663 735494 Fax: 01663 732744 Web: www.qedscientific.co.uk

